



Referencia	Dimensiones mm					Tornillos 12.9			Datos técnicos			
	Ød x ØD	H1	H2	H3	H4	n	M	Ma Nm	Mt Nm	Fax kN	Pa N/mm ²	Pm N/mm ²
RB1300.1/18x47	18 x 47	26	30	42	48	6	M6	17	510	57	322	123
RB1300.1/19x47	19 x 47	26	30	42	48	8	M6	17	540	57	305	123
RB1300.1/20x47	20 x 47	26	30	42	48	6	M6	17	570	57	290	123
RB1300.1/22x47	22 x 47	26	30	42	48	6	M6	17	620	57	263	123
RB1300.1/24x50	24 x 50	26	31	43	49	6	M6	17	680	57	241	116
RB1300.1/25x50	25 x 50	26	31	43	49	6	M6	17	710	57	232	116
RB1300.1/28x55	28 x 55	26	31	43	49	6	M6	17	790	57	207	105
RB1300.1/30x55	30 x 55	26	31	43	49	5	M6	17	850	57	193	105
RB1300.1/32x60	32 x 60	26	31	43	49	8	M6	17	1 200	76	241	129
RB1300.1/35x60	35 x 60	26	31	43	49	8	M6	17	1 300	76	221	129
RB1300.1/38x65	38 x 65	26	31	43	49	8	M6	17	1 400	76	203	119
RB1300.1/40x65	40 x 65	26	31	43	49	8	M6	17	1 500	76	193	119
RB1300.1/42x75	42 x 75	30	35,5	50,5	58,5	6	M8	41	2 200	100	221	124
RB1300.1/45x75	45 x 75	30	35,5	50,5	58,5	6	M8	41	2 400	100	206	124
RB1300.1/48x80	48 x 80	30	35,5	50,5	58,5	6	M8	41	2 500	100	193	116
RB1300.1/50x80	50 x 80	30	35,5	50,5	58,5	6	M8	41	2 600	100	185	116
RB1300.1/55x85	55 x 85	30	35,5	50,5	58,5	8	M8	41	3 800	140	225	145
RB1300.1/60x90	60 x 90	30	35,5	50,5	58,5	8	M8	41	4 200	140	206	137
RB1300.1/63x95	63 x 95	30	35,5	50,5	58,5	8	M8	41	4 400	140	196	130
RB1300.1/65x95	65 x 95	30	35,5	50,5	58,5	8	M8	41	4 500	140	190	130
RB1300.1/70x110	70 x 110	40	47	60	70	7	M10	83	7 000	200	190	121
RB1300.1/75x115	75 x 115	40	47	60	70	7	M10	83	7 500	200	178	116
RB1300.1/80x120	80 x 120	40	47	60	70	7	M10	83	8 000	200	167	111
RB1300.1/85x125	85 x 125	40	47	60	70	8	M10	83	9 800	230	179	122
RB1300.1/90x130	90 x 130	40	47	60	70	8	M10	83	10 300	230	169	117
RB1300.1/95x135	95 x 135	40	47	60	70	10	M10	83	13 600	290	200	141
RB1300.1/100x145	100 x 145	48	53	71	83	7	M12	145	15 000	300	173	119
RB1300.1/110x155	110 x 155	46	53	71	83	7	M12	145	16 500	300	157	112
RB1300.1/120x165	120 x 165	46	52	70	82	8	M12	145	20 500	342	164	119
RB1300.1/130x180	130 x 180	48	52	70	82	10	M12	145	27 600	427	190	137
RB1300.1/140x190	140 x 190	51	59	62	86	8	M14	230	32 600	466	173	128
RB1300.1/150x200	150 x 200	51	59	62	86	10	M14	230	43 700	583	202	152
RB1300.1/160x210	160 x 210	51	59	62	86	10	M14	230	48 600	583	189	144
RB1300.1/170x225	170 x 225	51	59	62	66	12	M14	230	59 400	699	214	162
RB1300.1/180x235	180 x 235	51	59	62	86	12	M14	230	62 900	699	202	155
RB1300.1/190x250	190 x 250	51	59	62	86	15	M14	230	83 000	874	239	162
RB1300.1/200x260	200 x 260	51	59	62	86	15	M14	230	87 400	874	227	175
RB1300.1/220x285	220 x 285	64	72	98	102	12	M16	355	104 700	952	179	138
RB1300.1/240x305	240 x 305	64	72	98	102	15	M16	355	142 800	1 190	205	162
RB1300.1/260x325	260 x 325	64	72	98	102	18	M16	355	185 600	1 428	228	162
RB1300.1/280x355	280 x 355	75	83	121	127	16	M18	485	215 500	1 539	194	153
RB1300.1/300x375	300 x 375	75	83	121	127	18	M18	485	259 700	1 731	204	163
RB1300.1/320x405	320 x 405	90	98	140	148	18	M20	690	358 300	2 240	206	163
RB1300.1/340x425	340 x 425	90	98	140	148	21	M20	690	444 200	2 613	226	181
RB1300.1/360x455	360 x 455	110	118	164	174	18	M22	930	493 600	2 742	184	145
RB1300.1/380x475	380 x 475	110	118	164	174	21	M22	930	607 800	3 199	203	162
RB1300.1/400x495	400 x 495	110	118	164	174	21	M22	930	639 8°	3 199	193	156

Ma: Par de apriete Mt: Par máximo transmisible Fax: Esfuerzo axial máximo transmisible Pa: Presión en el eje Pm: Presión en el alojamiento