



Referencia	Dimensiones mm					Tornillos 12.9			Datos técnicos			
	Ød x ØD	H1	H2	H3	H4	n	M	Ma Nm	Mt Nm	Fax kN	Pa N/mm²	Pm N/mm²
RB1710/14x32	14 x 32	14	18	21,5	25,5	4	M4	5	108	15	209	91
RB1710/15x32	15 x 32	14	18	21,5	25,5	4	M4	5	116	15	195	91
RB1710/16x32	16 x 32	14	18	21,5	25,5	4	M4	5	123	15	183	91
RB1710/18x47	18 x 47	17	22,5	28,5	34,5	5	M6	14	330	36	314	120
RB1710/19x47	19 x 47	17	22,5	28,5	34,5	5	M6	14	340	36	297	120
RB1710/20x47	20 x 47	17	22,5	28,5	34,5	5	M6	14	360	36	283	120
RB1710/22x47	22 x 47	17	22,5	28,5	34,5	5	M6	14	400	36	257	120
RB1710/24x50	24 x 50	17	22,5	28,5	34,5	6	M6	14	520	43	283	136
RB1710/25x50	25 x 50	17	22,5	28,5	34,5	6	M6	14	540	43	271	136
RB1710/28x55	28 x 55	17	22,5	28,5	34,5	6	M6	14	610	43	242	123
RB1710/30x55	30 x 55	17	22,6	28,5	34,5	6	M6	14	650	43	226	123
RB1710/32x60	32 x 60	17	22,5	28,5	34,5	8	M6	14	930	58	283	151
RB1710/35x60	35 x 60	17	22,5	28,5	34,5	8	M6	14	1 010	58	258	151
RB1710/38x65	38 x 65	17	22,5	28,5	34,5	8	M6	14	1 100	58	238	139
RB1710/40x65	40 x 65	17	22,5	28,5	34,5	8	M6	14	1 160	58	226	139
RB1710/42x75	42 x 75	20	26,5	34,5	42,5	7	M8	35	2 040	97	307	172
RB1710/45x75	45 x 75	20	26,5	34,5	42,5	7	M8	35	2 190	97	287	172
RB1710/48x80	48 x 80	20	26,5	34,5	42,5	7	M8	35	2 340	97	269	161
RB1710/50x80	50 x 80	20	26,5	34,5	42,5	7	M8	35	2 430	97	258	161
RB1710/55x85	55 x 85	20	26,5	34,5	42,5	8	M8	35	3 060	111	268	174
RB1710/60x90	60 x 90	20	26,5	34,5	42,5	8	M8	35	3 340	111	246	164
RB1710/63x95	63 x 95	20	26,5	34,5	42,5	9	M8	35	3 940	125	263	175
RB1710/65x95	65 x 95	20	26,5	34,5	42,5	9	M8	35	4 070	125	255	175
RB1710/70x110	70 x 110	24	30,5	40,5	50,5	8	M10	69	6 230	178	281	179
RB1710/75x115	75 x 115	24	30,5	40,5	50,5	8	M10	69	6 680	178	262	171
RB1710/80x120	80 x 120	24	30,5	40,5	50,5	8	M10	69	7 120	178	246	164
RB1710/85x125	85 x 125	24	30,5	40,5	50,5	9	M10	69	8 510	200	261	177
RB1710/90x130	90 x 130	24	30,5	40,5	50,5	9	M10	69	9 020	200	246	170
RB1710/95x135	95 x 135	24	30,5	40,5	50,5	10	M10	69	10 570	223	259	182
RB1710/100x145	100 x 145	26	33	45	57	8	M12	120	13 200	265	270	186
RB1710/110x155	110 x 155	26	33	45	57	8	M12	120	14 600	265	245	174
RB1710/120x165	120 x 165	26	33	45	57	9	M12	120	17 850	297	253	184
RB1710/130x180	130 x 180	34	41	55	69	9	M14	190	25 970	399	240	173
RB1710/140x190	140 x 190	34	41	55	69	9	M14	190	27 970	399	223	164
RB1710/150x200	150 x 200	34	41	55	69	10	M14	190	33 300	444	231	173
RB1710/160x210	160 x 210	34	41	55	69	11	M14	190	39 070	488	238	181
RB1710/170x225	170 x 225	44	51	65	79	12	M14	190	45 290	532	189	143
RB1710/180x235	180 x 235	44	51	65	79	12	M14	190	47 950	532	178	137
RB1710/190x250	190 x 250	44	51	65	79	15	M14	190	63 270	666	211	161
RB1710/200x260	200 x 260	44	51	65	79	15	M14	190	66 600	666	201	154
RB1710/220x285	220 x 285	50	57	73	89	12	M16	295	80 970	736	178	137
RB1710/240x305	240 x 305	50	57	73	89	15	M16	295	110 420	920	203	160
RB1710/260x325	260 x 325	50	57	73	89	18	M16	295	143 550	1 104	225	180
RB1710/280x355	280 x 355	60	67	85	103	16	M18	405	166 210	1 187	187	148
RB1710/300x375	300 x 375	60	67	85	103	18	M18	405	200 340	1 335	197	157
RB1710/320x405	320 x 405	74	82	102	122	18	M20	580	279 320	1 745	196	155
RB1710/840x425	840 x 425	74	82	102	122	21	M20	580	346 240	2 036	215	172
RB1710/360x455	360 x 455	86	94	116	138	18	M22	780	388 060	2 155	185	146
RB1710/380x475	380 x 475	86	94	116	138	21	M22	780	477 890	2 515	204	163
RB1710/400x495	400 x 495	86	94	116	138	21	M22	780	503 040	2 515	194	157

Ma: Par de apriete Mt: Par máximo transmisible Fax: Esfuerzo axial máximo transmisible Pa: Presión en el eje Pm: Presión en el alojamiento